## WTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N. 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O. Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

CLIENT : TOPDECK INTERNATIONAL PTY LTD

T/A TOPDECK FLOORING 1/14 CHURCHILL STREET SILVERWATER NSW 2128

: 7-598783-AN TEST NUMBER : 05/08/2014 ISSUE DATE PRINT DATE : 18/08/2014

SAMPLE DESCRIPTION Clients Ref: "Prime Registered Embossed 12.3mm

9901-10 Series" Laminated flooring

Colour tested: Lime, various colours available

Approximate Thickness: 12.3mm

Material Specification:

Clear paper cellulose wear layer impregnated with aluminium oxide and melamine/photographic decorative layer, HDF core impregnated with melamine, re-cycled paper base impregnated with melamine, paraffin waxed locking joints

Nominal total density: 850g/cm3 +/-20g/cm3

ASISO 9239.1-2003

Reaction to Fire Tests for Floorings Determination of the Burning Behaviour using a Radiant Heat Source

Date of sample arrival:

Date tested:

08/07/2014 04/08/2014

Results:

Length Width

	CH.	r value		
1	2	3	Mean	35272
5.4	4.9	4.9	5.1	kW/m2
8.9	17114525	45 - C-17		kW/m2
463616	COSELLA	73458695	1616901	27.75
272769		1	九十二十二十五十五十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十	DESCRIPTION OF THE PARTY OF THE

Smoke Value

2 3 Mean 5 5 Length 6

% min Width % min

Observations: Glowing

Note: Sample was conditioned in accordance with BSEN 13238-2001 at a temperature of 23+/-2degC and Relative Humidity of 50+/-5% for a minimum of 48 hours prior to testing

Each specimen was clamped to a substrate of 6mm fibre reinforced cement board prior to testing

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use

208184 END OF REPORT PAGE 1

© Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



This Laboratory is accredited by the National Association of Testing Authorities, Australia, for:
-Chemical Testing of Textiles & Related Products : Accreditation No. 983
-Mechanical Testing of Textiles & Related Products : Accreditation No. 985
-Heat & Temperature Measurement : Accreditation No. 1356

This document is issued in accordance with NATA's accreditation requirements. Samples, and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if ammended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved in advance by the Managing Director of AWTA Ltd.

APPROVED SIGNATORY

HAEL A. JACKSON B.Sc.(Hons)

LIMITEE